Katalog neu-2007.qxd:Katalog neu-2007.qxd 26.06.2007 13:48 Uhr Seite 55

DEUTSCH

Filament-Klebeband Sorte 850

Beschreibung

Die Sorte 850 besteht aus einer einseitig antiadhäsiv imprägnierten Polypropylenfolie, die mit einem sehr aggressiven Kleber beschichtet ist. Das Klebeband erlangt seine hohe Reißfestigkeit durch die eingearbeiteten Glasfasern. Die Sorte 850 ist beständig gegen Feuchtigkeit, verdünnte Laugen und Säuren.

Anwendung

Das hochreißfeste Klebeband 850 wird zur Sicherung von Packgütern, Paletten, Metall und Kunststoffrohren, sowie zum Bündeln aller stabförmigen Gegenstände verwendet. Die Sorte 850 geht mit Kartonagen eine feste Verbindung ein. Somit kann man das Klebeband nicht abziehen, ohne den Karton zu beschädigen. Dadurch ist ein zuverlässiger Schutz gegen Diebstahl gegeben.

Technische Daten

Träger	Polypropylenfolie glasfaserverstärkt
Gesamtdicke	120 µ
Dehnung bis Bruch	6 %
Klebkraft auf Stahl	25 N/25 mm
Zugfestigkeit	575 N/25 mm
Klebstoff	Hot melt
Temperaturbeständigkeit	bis 60° C
Kerndurchmesser	76 mm
Farbe	transparent
Länge	50 m

Verpackungseinheiten

Bandbreite mm	**Rollen pro Karton**
9	96
12	72
15	60
19	48
25	36
30	32
38	24
50	24

Andere Bandbreiten auf Anfrage

ENGLISH

Filament-Tape Type 850

Product Description

Type 850 consists of a PP foil, on one side impregnated with an anti-adhesive agent, coated with a very aggressive glue. The tensile strength of the tape is achieved by a glass-fibre reinforcement. Type 850 is resistant against moisture, thinned bases and acids.

Application

The highly tear proof tape 850 is used for securing of packages, pallets, metal and plastic tubes, as well as for bundling of oblong objects. Type 850 is securely bonding with cardboard. Removing of the tape is not possible, without destroying the carton, which is a reliable protection against theft.

Technical Data

Carrier	polypropylene foil fibre-glass reinforced
Carrier thickness	120 µ
Elongation at break	6 %
Adhesion on steel	25 N/25 mm
Tensile strength	575 N/25 mm
Glue	hot melt
Temperature resistance	up to 60° C
Core diameter	76 mm
Colour	transparent
Length	50 m

Packaging

Roll Width mm	**Rolls per carton**
9	96
12	72
15	60
19	48
25	36
30	32
38	24
50	24

Other roll widths available on request

MUSTER SAMPLE