Katalog neu-2007.qxd:Katalog neu-2007.qxd 26.06.2007 13:48 Uhr Seite 56

DEUTSCH

Filament-Klebeband Sorte 855

Beschreibung

Die Sorte 855 besteht aus einer einseitig antiadhäsiv imprägnierten Polypropylenfolie, die mit einem sehr aggressiven Kleber beschichtet ist. Das Klebeband 855 ist extrem reißfest und erhält dies durch die eingearbeiteten Glasfasern. Die Sorte 855 ist wasserdicht und beständig gegen Feuchtigkeit, verdünnte Laugen und Säuren.

Anwendung

Das Klebeband 855 ist extrem reißfest und eignet sich optimal zur Sicherung von palettierten Versandgut. Es können alle stabförmigen Gegenstände gebündelt und Schwerlasten abgesichert werden, sowie Packstücke aller Art verklebt und verstärkt werden. Die Sorte 855 geht mit Kartonagen eine feste Verbindung ein und ist somit ein zuverlässiger Schutz gegen Diebstahl.

Technische Daten

Träger	Polypropylenfolie glasfaserverstärkt
Gesamtdicke	140 µ
Dehnung bis Bruch	7 %
Klebkraft auf Stahl	25 N/25 mm
Zugfestigkeit	875 N/25 mm
Klebstoff	Hot melt
Temperaturbeständigkeit	bis 60° C
Kerndurchmesser	76 mm
Farbe	transparent
Länge	50 m

Verpackungseinheiten

Bandbreite mm	**Rollen pro Karton**
9	96
12	72
15	60
19	48
25	36
30	32
38	24
50	24

Andere Bandbreiten auf Anfrage

ENGLISH

Filament-Tape Type 855

Product Description

Type 855 consists of a PP foil, on one side impregnated with an anti-adhesive agent, coated with a very aggressive glue. The very high tensile strength of the tape 855 is achieved by a glass-fibre reinforcement. Type 855 is resistant against moisture, thinned bases and acids.

Application

Tape 855 has a very high tensile strength and ideally suits for securing of goods on pallets, bundling of oblong objects in bar form and securing of heavy-weight goods, as well as for gluing and reinforcing of any kind of packages. Type 850 is securely bonding with cardboard. Removing of the tape is not possible without destroying the carton, which is a reliable protection against theft.

Technical Data

Carrier	polypropylene foil fibre-glass reinforced
Carrier thickness	140 µ
Elongation at break	7 %
Adhesion on steel	25 N/25 mm
Tensile strength	875 N/25 mm
Glue	hot melt
Temperature resistance	up to 60° C
Core diameter	76 mm
Colour	transparent
Length	50 m

Packaging

Roll Width mm	**Rolls per carton**
9	96
12	72
15	60
19	48
25	36
30	32
38	24
50	24

Other roll widths available on request

MUSTER SAMPLE