Katalog neu-2007.qxd:Katalog neu-2007.qxd 26.06.2007 13:49 Uhr Seite 62

DEUTSCH

Gaffer-Tape Sorte 690

Beschreibung

Die Sorte 690 ist ein hochqualitatives PE-beschichtetes Gewebeklebeband mit einer sehr hohen Anfangshaftung. Durch die spezielle Kleber - beschichtung ist dieses Gaffer -Tape speziell im Außenbereich ideal und läßt sich problemlos rückstandsfrei von vielen Untergründen wieder ablösen. Es ist durch einen speziellen Kautschukkleber UV-stabil und läßt sich auch nach mehreren T agen rückstandsfrei entfernen. Das Klebeband ist reißfest, wasserdicht und sehr strapazierfähig. Kurz ein idealer Helfer für die Showindustrie. Die Sorte 690 ist in den Farben schwarz, weiß und silber erhältlich.

Anwendung

Die Sorte 690 dient als Langzeit-Gewebeklebeband für innen und aussen. Es besitzt sehr gute Klebeeigenschaften auf Holz, Teppichen, Kunststoff und Aluminium. Es ist UV -beständig und lässt sich rückstandsfrei von vielen Untergründen entfernen.

Technische Daten

Träger	PE-beschichtetes Gewebe
Gesamtdicke	300 µ
Dehnung bis Bruch	12 %
Klebkraft auf Stahl	11 N/25 mm
Zugfestigkeit	147 N/25 mm
Klebstoff	Naturkautschuk
Temperaturbeständigkeit	bis 90° C
Kerndurchmesser	76 mm
Farbe	weiß, schwarz, silber
Länge	50 m

Verpackungseinheiten

Bandbreite mm	**Rollen pro Karton**
50	24

Andere Bandbreiten auf Anfrage

Gaffer-Tape Type 690

ENGLISH

Product Description

Type 690 is a high-quality PE-coated cloth tape with very high tack. Due to its special coating with a natural rubber adhesive, this Gaffer tape is ideal for outdoor use. It sticks on almost any kind of surface and can be removed without leaving any residues - even after days. It is resistant to UV-light and to tearing, waterproof and very hard-wearing. T ype 690 is available in 3 colours: white, black and silver.

Application

Type 690 serves as cloth tape for long-term use in- and outdoors. It offers very good adhesive features for use with wood, carpets, plastics and aluminium. It is resistant against UV-light and can be removed from many kind of surfaces without leaving any residues.

Technical Data

Carrier	PE-coated cloth
Total thickness	300 µ
Elongation at break	12 %
Adhesion on steel	11 N/25 mm
Tensile strength	147 N/25 mm
Glue	natural rubber
Temperature resistance	up to 90° C
Core diameter	76 mm
Colour	white, black, silver
Length 50	m

Packaging

Roll Width mm	**Rolls per carton**
50	24

Other roll widths available on request

MUSTER SAMPLE